



Performance Lubricants Provide the Solution You Need

Product Guide

Industry	Krytox™ Lubricant	Temperature Range	Optimum Use Range	ISO Viscosity	Properties
Chemical – including reactive gases (F, O₂, Cl₂, HF)					
Valves	GPL 204	–60 °F to 355 °F –51 °C to 180 °C	–30 °F to 300 °F –35 °C to 149 °C	68	Safe in all reactive gases, including oxygen, chlorine, fluorine, and HF. Won't react with acids, bases, or other harsh chemicals. Won't oxidize or coke up.
Valves	GPL 206	–33 °F to 500 °F –36 °C to 260 °C	40 °F to 500 °F 5 °C to 260 °C	220	Safe in all reactive gases, including oxygen, chlorine, fluorine, and HF. Won't react with acids, bases, or other harsh chemicals. Won't oxidize or coke up.
Bearings	GPL 224	–60 °F to 355 °F –51 °C to 180 °C	–30 °F to 300 °F –35 °C to 149 °C	68	Safe for use with common acids, bases, solvents, and reactive gases. Won't wash out from water, steam, or solvents. Compatible with all seals.
Bearings	GPL 226	–33 °F to 500 °F –36 °C to 260 °C	40 °F to 500 °F 5 °C to 260 °C	220	Safe for use with common acids, bases, solvents, and reactive gases. Won't wash out from water, steam, or solvents. Compatible with all seals.
Bearings	XHT-ACX	14 °F to 572 °F –10 °C to 300 °C	50 °F to 572 °F 10 °C to 300 °C	680	H-1, very high temperature grease. Safe for use with common acids, bases, solvents, and reactive gases. Won't wash out from water, steam, or solvents.
Bearings	XHT-BDZ	23 °F to 750 °F –5 °C to 399 °C	550 °F to 725 °F 288 °C to 385 °C	1,000	Extreme high temperature grease.
Compressor oil	GPL 104	–60 °F to 355 °F –51 °C to 180 °C	–30 °F to 300 °F –35 °C to 149 °C	68	Safe around all chemicals. Compatible with all seals.
Vacuum pump fluid	VPF 1514	–65 °F to 320 °F –54 °C to 160 °C	–50 °F to 260 °F –45 °C to 126 °C	46	10 ⁻⁷ torr vapor pressure, compatible with all chemicals. H-1.
Corrugator					
Single facers	226 FG	–33 °F to 500 °F –36 °C to 260 °C	30 °F to 500 °F –1 °C to 260 °C	220	High temperature, long life high load carrying corrugator grease, H-1 food grade grease.
Single facers	227 FG	–22 °F to 550 °F –30 °C to 288 °C	40 °F to 550 °F 5 °C to 288 °C	460	High temperature, long life high load carrying corrugator grease, H-1 food grade grease.
Power Generation					
Steam Turbine Governor Control	XHT-ACX	–14 °F to 572 °F –10 °C to 300 °C	50 °F to 550 °F 10 °C to 288 °C	680	H-1, high performance, extreme pressure, and extreme high temperature anti-fretting grease.
Steam Turbine Governor Control	XHT-BDZ	23 °F to 750 °F –5 °C to 399 °C	550 °F to 725 °F 288 °C to 385 °C	1,000	High performance, extreme pressure, and extreme high temperature anti-fretting grease.

Industry	Krytox™ Lubricant	Temperature Range	Optimum Use Range	ISO Viscosity	Properties
Power Generation (continued)					
Turbine Frame Expansion Bearing	XHT-BDZ	23 °F to 750 °F -5 °C to 399 °C	550 °F to 725 °F 288 °C to 385 °C	1,000	Extreme high temperature grease.
Valves	GPL 204	-60 °F to 500 °F -51 °C to 260 °C	-30 °F to 300 °F -35 °C to 149 °C	68	Safe in all reactive gases, including oxygen, chlorine, fluorine, and HF. Won't react with acids, bases, or other harsh chemicals. Won't oxidize or coke up.
Valves	GPL 206	-33 °F to 500 °F -36 °C to 260 °C	40 °F to 500 °F 5 °C to 260 °C	220	Safe in all reactive gases, including oxygen, chlorine, fluorine, and HF. Won't react with acids, bases, or other harsh chemicals. Won't oxidize or coke up. H-1
Bearings	GPL 224	-60 °F to 355 °F -51 °C to 180 °C	-30 °F to 300 °F -35 °C to 149 °C	68	Safe for use with common acids, bases, solvents, and reactive gases. Won't wash out from water, steam, or solvents. Compatible with all seals.
Bearings	GPL 226	-33 °F to 500 °F -36 °C to 260 °C	40 °F to 500 °F 5 °C to 260 °C	220	Safe for use with common acids, bases, solvents, and reactive gases. Won't wash out from water, steam, or solvents. Compatible with all seals.
Food Processing					
Valves	GPL 205	-33 °F to 400 °F -36 °C to 204 °C	0 °F to 350 °F -18 °C to 177 °C	150	H-1, inert, compatible with all seals and packing.
Bearings	GPL 223	-76 °F to 310 °F -60 °C to 155 °C	-50 °F to 250 °F -45 °C to 121 °C	32	H-1, ambient temperature.
Bearings	GPL 226 or FG 34	-33 °F to 500 °F -36 °C to 260 °C	0 °F to 500 °F -18 °C to 260 °C	220	H-1, high temperature.

The information set forth herein is furnished free of charge and based on technical data that Chemours believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Because conditions of product use are outside our control, Chemours makes no warranties, express or implied, and assumes no liability in connection with any use of this information. As with any material, evaluation of any compound under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF CHEMOURS.

For product information, industry applications, technical assistance, or global distributor contacts, visit krytox.com or within the U.S. and Canada, call 1-844-773-CHEM/2436 or outside of the U.S., call 1-302-773-1000.

© 2015 The Chemours Company FC, LLC. Krytox™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Replaces: K-15429-6
C-10060 (7/15)