



Corrugator Greases—NSF H-1 Food Grade Registered

Product Information

Krytox™—Setting the Standard for the Corrugating Industry

Since the 1980s, Krytox™ anti-corrosion greases have set the standard for high temperature bearing lubrication in corrugator applications. These products are the same high performance formulation the corrugated industry has trusted for years, and, we are pleased to announce, are now registered for incidental food contact.

NSF Registration Means Safety and Confidence

To provide absolute confidence and safety in food-related operations, these products are NSF H-1 food grade registered. Corrugator Krytox™ 226FG¹ and Corrugator Krytox™ 227FG² provide you with peace-of-mind and full confidence that Krytox™ greases are non-toxic and completely biologically and environmentally inert.

Krytox™ corrugator greases are recommended for use in high temperature corrugated equipment applications and manufacture of food packaging materials where an H-1 rated lubricant is required.

Property	Corrugator Krytox™ 226FG	Corrugator Krytox™ 227FG
NLGI Grade	2	2
ISO Grade of Base Oil	220	460
Specific Gravity	1.95	1.95
Oil Separation, %, 30 hr at 99 °C (210 °F)	3	3
Anti-Corrosion Additive	Sodium Nitrite	Sodium Nitrite
Coefficient of Friction, ASTM D2266	0.11	0.11
Thickener	PTFE	PTFE
Appearance	White, creamy consistency	White, creamy consistency
Base Oil Viscosity, cSt at 40 °C (104 °F) at 100 °C (212 °F)	240 25	440 42
Viscosity Index	134	155
Operating Range, °C (°F)	-36-260 (-33-500)	-30-288 (-22-550)
Rust Prevention, ASTM D1743	Pass	Pass
Four Ball Wear Scar, ASTM D2266 at 1 hr, 1200 rpm, 107 °C (225 °F), 20 kg	0.4 mm	0.4 mm
Oil Volatility, %, 22 hr at 204 °C (400 °F) ASTM D2595	3 max.	1 max.

¹Krytox™ 226FG is NSF135659 registered. ²Krytox™ 227FG is NSF135660 registered.



Reliability and Performance for Your Most Demanding Needs

High temperature, extreme pressure Krytox™ greases excel in the most demanding environments. Their non-oxidizing chemistry and wide temperature range allows them to be used in temperature extremes. Its superior oil film strength reduces friction and abrasive wear to significantly extend equipment life in severe duty applications. Krytox™ provides excellent water washout resistance and superior rust and corrosion protection for bearings and components. Krytox™ is silicone-free, contains no VOC materials or chlorine, and is not hazardous to the atmosphere or ozone layer.

Chemical and Environmental Compatibility

While Krytox™ fluorinated greases are non-reactive, its PFPE chemistry is very different from standard hydrocarbon or synthetic chemistries and should never be mixed with non-fluorinated greases.

Krytox™ lubricants are inert and will not react with any materials they may come in contact with. The polymeric nature of these products is extremely resistant to moisture, so it stays in place during cleaning. Cleaners and disinfectants, both acidic and caustic types, do not affect them. Steam and high temperatures will not damage them. They do not damage plastic or elastomer seals or cause corrosion to metals. They are nonflammable and safe for use in oxygen service.

Packing the Bearing

New bearings should be inspected for damage and cleanliness before use. New unlubricated bearings are often coated with hydrocarbon-based rust preventive oils to protect them during storage. These preservative oils must be removed when using Krytox™ as a lubricant. Failure to do so could result in reduced bearing life.

The preservatives coat the bearing surface to prevent rust and corrosion, but, if not removed prior to use, will prevent the grease from protecting the metal surface. If left on the bearing, the preservative coating can oxidize and harden and create debris that will contaminate the grease.

Storage and Shelf Life

Krytox™ grease and oil lubricants have no expiration date and an indefinite shelf life if unopened and stored in a clean, dry location.

The information set forth herein is furnished free of charge and based on technical data that Chemours believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Because conditions of product use are outside our control, Chemours makes no warranties, express or implied, and assumes no liability in connection with any use of this information. As with any material, evaluation of any compound under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF CHEMOURS.

For product information, industry applications, technical assistance, or global distributor contacts, visit krytox.com or within the U.S. and Canada, call 1-844-773-CHEM/2436 or outside of the U.S., call 1-302-773-1000.

© 2017 The Chemours Company FC, LLC. Krytox™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Replaces: K-08980-1
C-10280 (7/17)